

Strength on all fronts™

DS Warranty

November 2022



DS Stålprofil
Quality. Strength. Since 1969.

Warranty terms and conditions

- The product must not be used in particularly corrosive or aggressive environments, e.g. in air with a high salt content, be in constant contact with water or in contact with e.g. chemicals, smoke, copper, lead, manure, dust, ash and other external corrosion-causing elements.
- The product must not come into contact with wet concrete, wet timber and pressure-impregnated wood.
- The product must be installed in accordance with DS Stålprofil's installation instructions.
- The product must be installed using DS Fittings and DS Sealing Accessories.
- The product must be maintained and inspected in accordance with the applicable guidelines issued by DS Stålprofil A/S.
- The product is installed at the correct roof pitch.
- The product is not exposed to mechanical effects after it has left the factory.
- Products in a rain shadow must be washed in the correct way.
- The product must be stored correctly before it is installed and installed not more than one month after the invoice date.
- The current owner must be able to submit written documentation that describes the order and/or the invoice number or other proof of purchase.
- A complaint must be submitted to DS Stålprofil A/S no later than three weeks from when the damage was discovered or from when it should have been discovered.
- DS Stålprofil A/S must have the opportunity to inspect the product while it is installed.

Compensation terms and conditions

- When an entitled claim is received in accordance with the warranty terms and conditions, and depending on the evaluation of the product, DS Stålprofil A/S will choose to either recoat the product or supply new products as a replacement for the defective products.
- Liability related to this warranty is limited to the original invoice value and does not cover the costs of removal or re-installation.
- DS Stålprofil A/S is not liable for direct or indirect losses, including production losses, rent losses, consequential damages and damages to the other parts of the building structure or buildings.
- The warranty for the replacement or re-coating of products applies during the remaining period of the original warranty.
- The warranty does not apply to colour differences when products are replaced.
- The warranty does not cover any corrosion formation at sheet edges and around perforations of products.
- The warranty does not apply to the coating on the rear of the products.

Please note that tension-induced bulging in thin plate steel is not covered by the warranty.



Denmark's best warranty terms and conditions.

At DS Stålprofil, you get a full 30-year warranty. This means that the coverage is the same from the first to the last day of the warranty period – even for holiday homes located on the coast.



Warranty steel sheets

This warranty is issued by DS Stålprofil A/S. The warranty covers in-house manufactured steel sheets, which during the warranty period have developed corrosion holes as a consequence of defects in manufacture or materials.

The warranty applies from the date of purchase and covers the following products:

- DS Trapezoidal 20-115
- DS Trapezoidal 35-206
- DS Trapezoidal 35-190
- DS Trapezoidal 45-333 S
- DS Sinusoidal 18-75
- DS Sinusoidal 35-143
- DS Rib Sheet 22-270
- DS Inverted Rib Sheet 22-270
- DS Unique 400
- DS Distinct 350
- DS Distinct 460
- DS Distinct 1050
- DS Distinct 1070
- DS Premium Facade Panel
- DS Nordic Click Seam

50 µm GreenCoat Pural BT: 30-year warranty

50 µm GreenCoat Pural BT Matt: 30-year warranty

36 µm GreenCoat Pro BT Matt: 30-year warranty

36 µm Pladur Ice Crystal: 25-year warranty

25 µm Polyester: 20-year warranty

Aluzink AZ 185+: 20-year warranty

If used in an area within 10 km of the coastline, the warranty period is halved. However, if Aluzink is used in an area within 10 km of the coastline, it is not covered by the warranty.

Please note that the warranty does not cover products that are perforated.

It is recommended that stainless fittings are used with installations in an area within 10 km of the coastline.

This warranty applies to all deliveries made from January 2020.

Warranty light sheets

This warranty is issued by DS Stålprofil A/S. The warranty covers PVC and PC light sheets, which during the warranty period must have a light transmission of less than 70%.

The warranty applies from the date of purchase and covers the following products:

- DS Trapezoidal 20-115
- DS Trapezoidal 35-206
- DS Trapezoidal 35-190
- DS Trapezoidal 45-333 S
- DS Sinusoidal 18-75
- DS Sinusoidal 35-143
- DS Rib Sheet 22-270
- DS Unique 400
- DS Distinct 1050
- DS Distinct 1070



PVC Light sheets: 5-year warranty
PC Light sheets: 10-year warranty

This warranty applies to all deliveries made from January 2020.

Warranty gutter range

This warranty is issued by DS Stålprofil A/S. The warranty covers gutters, downpipes and fittings, which during the warranty period have developed corrosion holes as a consequence of defects in manufacture or materials.

The warranty applies from the date of purchase and covers the following products:

- DS Gutters
- Downpipes
- DS fittings for gutter range



50 µm Nova: 20-year warranty
Aluzink: 15-year warranty

This warranty applies to all deliveries made from January 2020.

Maintenance

To ensure the optimal use of steel sheet cladding, it is important that the maintenance stated below is followed. The following points must be checked by inspection:

- 1 There is no dirt accumulations and all of the cladding is clean.
- 2 The cladding is intact. Particular attention is paid to cutting edges.
- 3 Screws and other fittings have not become loose
- 4 Flashing is secure, edges sealed with the surrounding materials.
- 5 Rib strip is correctly in place for optimal sealing.
- 6 Any damage that has occurred is immediately repaired.

Cleaning

It is important that the cladding is cleaned at suitable intervals, however at least once a year. Note that some exterior surfaces may be located in a rain shadow, e.g. facade cladding underneath an overhang. These surfaces must be cleaned more often otherwise greater soiling can build up because there has not been any natural rinsing from rain.

Dirt deposits and similar may be washed off using a soft brush and mild soapy water.

DS Stålfamiljen takes care of the environment

DS Stålfamiljen does not use or manufacture products that pollute or adversely affect the environment where they shall be used. All of the products and structural elements can be disposed of, destroyed or recycled in a way that is completely safe for the environment.

DS Stålfamiljen does not use chemicals that are hazardous to health if the work can be carried out in a sensible way without the use of such chemicals.



Find inspiration on
www.ds-staalprofil.com

Steel is perfect for roofs and facades. Above all, because steel is strong. This means you get a unique solution that has a long lifetime, which protects your building optimally – and requires a minimum of maintenance. At the same time, roof and facade solutions from DS Stålprofil provide you with the freedom to precisely create the look you want.

Strength on all fronts™



DS Stålprofil

DS Stålprofil A/S
Andrupvej 9 · DK-9500 Hobro
Tel.: +45 96 57 28 28
www.ds-staalprofil.com

DEALER: